

Mohawk

Finishing Products, Inc.

Product Data Sheet

WOOD REPAIR SOLVENT

M740-200

Available in pints and gallons

Product Description: Mohawk's "Wood Repair Solvent" is used to return the pliability and workability to Mohawk's "Wood Repair" product line M740. As in a thickened putty, due to solvent evaporation, a small amount of solvent is all that is needed to return the putty to its original viscosity.

Advantages:

1. Provides quick results.

Product Limitations:

1. For use with a Mohawk product only.

Characteristics:

Weight per gallon: 6.79 ± 0.1 lbs./gal.

Flashpoint: 8 F/-13 c

Package Viscosity: 22-24 seconds #1 Zahn cup

Volatile Organic Compounds (VOC): Not to exceed 764 grams/liter, 6.38 lbs./gal.

Spec. Gravity: 0.816 ± 0.01

Non Volatile (wt.) $4.7 \pm 0.02\%$

Package Life: 2 years

Boiling Range: 135 F/57 c

Air Quality Data: Non-Photochemically Reactive

Hazardous Air Pollutants: 0.75 lbs. max./1 lb. Solids

HMIS:

Health: 1

Flammability: 4

Reactivity: 0

Personal Protection: B

Specifications:

Directions: A balanced blend of solvents to maintain or reconstitute the workability of filler products. Avoid excess, add solvent in small increments, work solvent with spatula into filler until desired consistency is reached. Excess solvent will increase filler shrinkage. A second application of filler would become necessary.

Safety Cautions: Contents are EXTREMELY FLAMMABLE. Vapors may ignite EXPLOSIVELY. Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated. Avoid breathing of vapor and spray mist. USE ONLY WITH ADEQUATE VENTILATION. Avoid contact with skin and eyes. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products, Inc.

4715 State Highway 30

Amsterdam, NY 12010-7417

Phone: 518-843-1380

Fax: 518-842-3551