

Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

Product Data Sheet

Epoxy Putty Stick

M743- all colors

Product Description: The Mohawk Epoxy Stick is a compound that will make a permanent repair and create the reshaping/replacing of wooden parts for general restoration. After a 20 minute cure time (3-6 minutes working time, depending on color) the repaired area is hard enough to be subjected to sanding, drilling, staining and general finishing.

Advantages:

1. Makes durable and permanent repairs.
2. Three to six minute working time.
3. No shrinkage.
4. Excellent adhesion.

Characteristics:

Appearance: solid putty, color(s)

Shrinkage: <1%

Flash point: none observed

Dry/Cure time: Air dry @ 72° F, 35% relative humidity

Working time: 3-6 minutes (depending on color)

Cure time: 20 minutes

Non-Volatile Content: 100%

VOC's (coating): 0.0 lbs/gal (0.0 g/l)

VOC's (material): 0.0 lbs/gal (0.0 g/l)

Package life: Two years minimum from date of shipment when stored in original, unopened container in a dry area at temperatures below 75°F (24°C)”

HMIS: Health – 2, Flammability – 1, Reactivity – 0, Personal Protection – X

Specifications:

Directions: Surface preparation – For best adhesion sand to roughen surface and to remove any loose paint, dirt or other contaminants. Although dry surfaces are preferred, Epoxy Putty Stick will adhere to damp surfaces.

Mixing & Application:

1. Trim end and discard. Break/cut off required amount.
2. Knead in the hands (see cautions*) or mix with putty knife until a uniform color is achieved. Mix only what can be used in 6 minutes.
3. Apply mixed compound within 6 minutes for optimum adhesion and to avoid premature hardening. Firmly work into the surface.

4. Wet fingers with tap water and rub into putty surface for maximum workability. Shape as desired. Strike off nail holes and the like with wet putty knife.
5. May be sanded and stained or painted after material has hardened, within 20 minutes.
NOTE: Sanding greatly increases stainability. Sanding is easiest within first few hours of application.

Safety and Other Precautions: Read MSDS for precautions before using product.

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

P.O. Box 22000

Phone: 1-800-545-0047

Hickory, NC 28603

Fax: 1-800-721-1545

INFORMATION and LIMITED WARRANTY DISCLAIMER

To the best of our knowledge the technical data contained herein is true and accurate on the date of publication and is subject to change without prior notice. User must contact Mohawk Finishing Products to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We assume no responsibility for coverage, performance or injuries resulting from use. The data on this sheet represents estimated and typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. We sell the products without warranty. Users assume all responsibility and liability for use. Loss or damage arising from the use of our products whether used alone or in combination with our products is the responsibility of the user. **MOHAWK FINISHING PRODUCTS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. MOHAWK FINISHING PRODUCTS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. The information on this sheet, as well as the products referenced herein, shall be considered "Confidential Information". Wet samples and uncured samples of these products shall be maintained as confidential and shall not be disclosed to any third party without the prior written permission of Mohawk Finishing Products.