

Mohawk Finishing Products

A Division of RPM Wood Finishes Group, Inc.

Product Data Sheet

FM Slip Additive

M850-20394

8.5 fl. oz. bottle

Product Description: FM Slip Additive is added to Top Coat to adjust the feel of the leather coating. Hands and clothing will slide more easily on the surface of the leather.

Characteristics:

Physical state: Liquid

Package life: Maximum 1 year from date of manufacture, must be kept in original container.

Storage: Protect from freezing. Store above 40° F.

Health: 2

Flammability: 1

Reactivity: 0

Personal Protection: B

Specifications:

Leather type usage:

Pre-test: Apply the mixture of the Top Coat and FM Slip Additive in a hidden area. (FM Non-Slip Additive may be mixed in as well). Allow to dry. Check to be sure the feel of the leather is as intended.

Directions: Mix FM Slip Additive into the Top Coat at a rate no greater than 1%. Apply Top Coat according to directions.

Safety cautions: Use only in a well ventilated area. Avoid contact with eyes, skin and clothing. Avoid breathing vapor. Additional local exhaust ventilation is recommended where mists or vapors may be released.

KEEP OUT OF REACH OF CHILDREN

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

P O Box 22000

Hickory, NC 28603

Phone: 1-800-545-0047

Fax: 1-800-721-1545