

# Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

## Product Data Sheet

### Base Coat (neutral and colors)

M850 - all colors

1 quart

**Product Description:** Base coat is used as a base coat to add color in the reconstruction of pigmented leather.

### Characteristics:

Viscosity: 750-1050 cps

Solids (wt %): 31.97 \*

Solids (vol %): 28.56\*

Dry time: 30 - 45 minutes to handle or recoat

Package life: 1 year from date of manufacture. Must be kept in original container.

\* = varies depending on color

Storage: Protect from freezing. Store above 40° F.

HMIS: Health: 2, Flammability: 1, Reactivity: 0, Personal Protection: X

### Specifications:

**Instructions:** Use Base Coat for adding color in reconstruction of pigmented leather. Shake well. Test in a hidden area to check color match. If not satisfied, remix to achieve desired hue. (Note: A 6% add of Crosslinker will increase the adhesion and final rub resistance; leather may dry a bit harder). Prepare leather by applying Adhesion Promoter. Apply Base Coat while Adhesion Promoter is tacky. Hand pad Base Coat with cloth or foam, filling all cracks, pleats and creases. Thoroughly dry in pleats and creases so leather does not stick together. Spray light coat on entire area to be covered, in crisscross pattern and allow to dry completely. A hair dryer will speed drying. Make sure color has been applied uniformly. If necessary, apply additional coat. When dry, apply topcoat to creases and pleats as above. When creases are dry, spray apply Top Coat to the entire area. Crosslinker MC will make the Top Coat more resistant to abrasion wear.

## Safety cautions:

Principal Hazards: Warning! Causes eye and skin irritation. Vapor harmful.

Contents: water, proprietary polyurethane resin solids, dipropylene glycol monomethyl ether, acrylic non volatiles, isopropanol, triethanolamine

Other Hazards: Causes lung, eye, skin, nose and throat irritation.. Overexposure may cause liver, kidney damage. Use only with adequate ventilation. Vapor harmful, May affect the brain or nervous system causing dizziness, headache or nausea. Harmful if swallowed.

Precautions: do not breathe vapors. Keep away from heat, sparks and flame. Use only with adequate ventilation. Do not get in eyes, on skin or clothing.

First Aid: If affected by product, remove to fresh air. If swallowed, do not induce vomiting. Flush eyes or skin immediately with plenty of water. If exposure occurs, get medical attention immediately.

**KEEP OUT OF REACH OF CHILDREN.**

For industrial & commercial use only.

See material Safety Data Sheet (MSDS) for complete information and First Aid.

**MSDS:** If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

P O Box 22000

Hickory, NC 28603

Phone: 1-800-545-0047

Fax: 1-800-721-1545