

Mohawk Finishing Products

A Division of RPM Wood Finishes Group, Inc.

Product Data Sheet

Pigment Touch-Up

M850-all colors

8 fl. oz. bottles

Product Description: Pigment Touch-Up is a single step product that combines fixation, adhesion, light filling properties, pigment and topcoat all in one easy to use product. It exhibits high performance specs for dry rubbing, wet rubbing and flexibility. It is the final step in covering repairs on pigmented leathers with color and/or sheen adjustment. Most often, it is used over a damaged area that has been repaired with Mohawk Leather Glue or Repairing Paste.

Characteristics:

Physical state: Liquid

Package life: Maximum 1 year from date of manufacture, must be kept in original container.

Storage: Protect from freezing. Store above 40° f.

HMIS:

Health: 2

Flammability: 1

Reactivity: 0

Personal Protection: B

Specifications:

Leather type usage: Use pigment Touch-Up on pigmented leathers (Mohawk supplies separate Color Revives for aniline and nubuck leathers).

Pre-test: Shake before testing. Test the color and sheen matches in a hidden area, using good lighting. Colors may be intermixed to achieve the proper hue. Mohawk Dulling Agent may be added to lower the sheen if necessary. Allow the product to dry before

making the evaluation because the color tends to lighten slightly as it dries. A hair dryer may be used to speed drying.

Directions: Shake well before using. Colors may be intermixed to achieve the proper hue. Mohawk Dulling Agent may be added to lower the sheen if necessary. Apply a small amount of Pigment touch-Up to a soft cloth or a sponge. Lightly dab the spot to be colored. Use a hair dryer to dry each layer before applying another. Continue until the repair is completely colored. If needed, additional blending can be achieved by mixing some of the matched color with Leather Protector and feathering the mixture in each direction with a cloth. Allow to dry. Massage the leather to enhance the grain effect.

Routine care: Use Leather Cleaner and Leather Protector regularly for cleaning and protection.

Safety cautions: Use only in a well ventilated area. Avoid contact with eyes, skin and clothing. Avoid breathing vapor. Additional local exhaust ventilation is recommended where mists or vapors may be released.

KEEP OUT OF REACH OF CHILDREN.

MSDS: If Material Safety Data Sheet is required, contact:
Mohawk Finishing Products
Division of RPM Wood Finishes Group, Inc.
Hickory, NC 28603

Phone: 1-800-545-0047
Fax: 1-800-721-1545