

Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

Product Data Sheet

Ultra® Penetrating Stain Architectural

MA520- (Color)

Available in 1 quart, 1 gallon

Product Description: Mohawk Ultra® Penetrating Stains are superior dye stains designed for use on furniture and cabinets. They're non-grain raising stains that offer superior transparent qualities found only in dye stains. They also feature excellent light fastness and will not bleed into topcoat finishes.

Advantages:

1. 120 VOC compliant.
2. Enhances the natural beauty of wood grain.
3. Prematched in colors similar to Mohawk's M545 Wood Wiping Stains.
4. Colors can be intermixed to achieve other shades.
5. Highly fade and UV resistant colors (not intended for exterior applications).
6. Non-bleeding when topcoated with most solvent-borne topcoats. Color bleeding should be checked when topcoated with water-borne topcoats.
7. Stain clean up may be done with water.
8. Color intensity may be adjusted with M520-0001 Ultra® Penetrating Stain Reducer.
9. Open time of stain can be increased by addition of M520-0002 Ultra® Penetrating Stain Retarder.

Characteristics:

Weight per gallon: 6.80 – 6.98 lbs/gal

Solids % (wt): 0.38 – 3.16

Solids % (vol): 0.23 – 2.12

Dry time: Air dry @ 77F and 50% RH

To handle: 15 minutes

To recoat: 30 minutes

VOC's (material): 1.00 lbs/gal (120.0 g/l max.)

VHAP's: 0.0 – 0.59 lbs VHAP's/lb solids (HAPs compliant)

Coverage: 250 sq. ft

Package life: 3 years

HMIS: Health – 3, Flammability – 3, Reactivity – 0, Personal Protection - B

Specifications:

Directions: Ultra Penetrating Stain® may be brushed, wiped or spray-applied (approximately 30-35 psi). Reduce with Ultra® Penetrating Stain Reducer (M520-00017) to adjust color strength. Drying time may be slowed with Ultra® Penetrating Stain Retarder (M520-00026). Ultra® Penetrating Stain may also be added to nitrocellulose lacquers for shading. (Do not exceed 8 oz. per gallon.)

Surface must be clean, dry, wax-free and finish sanded no finer than 220 grit. Remove sanding dust with tack cloth or vacuum. Ultra® Penetrating Stain may be brushed, wiped or spray applied (approximately 30-35 psi). When wiping, stain should be applied with the grain in a wet uniform consistency. Allow the stain to penetrate; then wipe off excess stain with a lint free cloth. Ultra™ Penetrating Stain is recommended for use without

reduction, however it may be reduced with Ultra® Penetrating Stain Reducer (M520-00017) to adjust the color strength. Allow the stain to thoroughly dry before topcoating. Drying time may be slowed with Ultra® Penetrating Stain Retarder (M520-00026). Ultra® Penetrating Stain may also be added to nitrocellulose lacquers for shading. (Do not exceed 8 fl. oz. per gallon.) Clean up with water or Ultra® Penetrating Stain Reducer.

Safety and Other Precautions: Read MSDS for precautions before using product.

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products
Division of RPM Wood Finishes Group, Inc.

P.O. Box 22000 Phone: 1-800-545-0047
Hickory, NC 28603 Fax: 1-800-721-1545

INFORMATION and LIMITED WARRANTY DISCLAIMER

To the best of our knowledge the technical data contained herein is true and accurate on the date of publication and is subject to change without prior notice. User must contact Mohawk Finishing Products to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We assume no responsibility for coverage, performance or injuries resulting from use. The data on this sheet represents estimated and typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. We sell the products without warranty. Users assume all responsibility and liability for use. Loss or damage arising from the use of our products whether used alone or in combination with our products is the responsibility of the user. **MOHAWK FINISHING PRODUCTS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. MOHAWK FINISHING PRODUCTS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. The information on this sheet, as well as the products referenced herein, shall be considered "Confidential Information". Wet samples and uncured samples of these products shall be maintained as confidential and shall not be disclosed to any third party without the prior written permission of Mohawk Finishing Products.