

Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

Product Data Sheet

Pre-Charged Aerosol, Coatings, Toners, Solvents

M121-0001

Product Description: Mohawk Pre-Charged Aerosol cans are used where there is a need for on-site filling of aerosols with customer's bulk product. Pre-Charged Aerosols are convenient, quick and easy to use, and work with most filling machines. Always test for compatibility.

Characteristics:

Weight per gallon: 5.41 lbs/gal (including propellant)

Solids % (wt): 0

Solids % (vol): 0

Package viscosity: 20-25 seconds, #1 Zahn cup

VOC's (coating): 4.91 lbs/gal (589.70 g/l)

VOC's (material): 3.49 lbs/gal (418.66 g/l)

% Wt VHAP's: 0

Package life: 3 years

HMIS: Health – 2, Flammability – 4, Reactivity – 0, Personal Protection – X

Specifications:

Directions: SHAKE WELL BEFORE USING to ensure color and sheen uniformity. Point opening of spray button toward object, holding can 12 to 14 inches away from surface to be coated. Press spray button firmly. Clean spray button immediately by spraying with can upside down until no more product comes out. If clogged, remove spray button with a twisting motion and clean. Gently twist button onto can with opening turned away from you.

Note: Recommended for use with most solvent based coatings, NGR stains, toners and solvents. Manufacturer has only filled solvent and propellant. For more specific information, please reference MSDS of material filled. Always test first can filled in an inconspicuous area to ensure desired performance.

Safety Cautions:

Principle Hazards: Danger! Extremely flammable liquid and vapor. Vapors may cause flash fire. Causes Eye and skin irritation. Harmful if swallowed. Vapor harmful.

Other Hazards: Causes eye, skin, nose and throat irritation. Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. May be harmful if absorbed through skin. Harmful if swallowed.

Precautions: **KEEP OUT OF REACH OF CHILDREN.** Wash thoroughly after handling. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirators manufacturer's directions for respirator use. Use only with adequate ventilation. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Do not get in eyes, on skin or clothing. Vapors may ignite explosively. Do not breathe dust, vapors or spray mist. Keep away from heat, sparks and flame.

First Aid: If swallowed, do not induce vomiting. Get medical attention immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Clean contaminated shoes.

Handling: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products
Division of RPM Wood Finishes Group, Inc.
P O Box 22000
Hickory, NC 28603

Phone: 1-800-545-0047
Fax: 1-800-721-1545